

# Twin hole pre-rinse set with mixer

Ref. G6532

With bib tap and swivelling telescopic spout

## DESCRIPTION

**Twin hole pre-rinse set with mixer - Ref. G6532**

Complete pre-rinse set with bib tap suitable for intensive use in professional kitchens.

Deck-mounted twin hole mixer with adjustable centres from 100 - 240mm with:

- valve heads with control knobs.
- offset inlet connections with M1/2" tails.
- mixer supplied with non-return valves

Bib tap with telescopic, swivelling spout L. 200 - 290mm.

- 20 lpm flow rate at the outlet.

- valve head with control knob.

White hand spray with adjustable jet and 9 lpm flow rate at the outlet (ref. 433000).

Scale-resistant hand spray and shock-resistant tip.

Reinforced, food-grade, white flexible hose L. 0.95m.

3/4" stainless steel column.

Adjustable wall bracket.

Stainless steel spring guide.

Pre-rinse set.

30-year warranty.

These pre-rinse sets can be installed close to the splashback.

## TECHNICAL CHARACTERISTICS

**Twin hole pre-rinse set with mixer - Ref. G6532**

|                   |                                                                                                                                                                                                                                                                                                                                                 |
|-------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connector         | M1/2"                                                                                                                                                                                                                                                                                                                                           |
| Height            | 1120 - 1240mm                                                                                                                                                                                                                                                                                                                                   |
| Drop height       | Bib tap: 275mm, hand spray: 475 - 595mm                                                                                                                                                                                                                                                                                                         |
| Flow rate         | 20 lpm with the bib tap; 9 lpm via the hand spray                                                                                                                                                                                                                                                                                               |
| Width to the wall | 35 - 162mm                                                                                                                                                                                                                                                                                                                                      |
| Finish            | Stainless steel                                                                                                                                                                                                                                                                                                                                 |
| Norms             |     |
| Warranty          |                                                                                                                                                                                                                                                              |
| Repairability     |                                                                                                                                                                                                                                                              |



## ADVANTAGES



Rapid fill: full flow rate 20 lpm



Telescopic, swivelling rapid-fill spout



Increased resistance: water-free valve heads



Anti-torsion rotating nuts and PVC sheath

