Mechanical mixer for sinks or troughs

Ref. 2510T

Single hole mechanical mixer with swivelling spout H. 155mm L. 230mm



ADVANTAGES

Mechanical mixer for sinks or troughs - Ref. 2510T Deck-mounted mechanical sink mixer. Single hole mechanical mixer with swivelling spout H. 155mm L. 230mm fitted

Single hole mechanical mixer with swivelling spout H. 155mm L. 230mm fitted with hygienic flow straightener.

Spout suitable for fitting a BIOFIL point-of-use filter.

 $\ensuremath{\text{\emptyset}}$ 40mm standard ceramic cartridge with pre-set maximum temperature limiter.

Body and spout with smooth interiors.

Flow rate limited to 9 lpm at 3 bar.

Solid control lever.

DESCRIPTION

Supplied with PEX flexibles F3/8".

Fixing reinforced by 2 stainless steel rods.

Mechanical mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Single hole mixer suitable for people with reduced mobility.

30-year warranty.



Hygiene: smooth interior reduces bacteria



Pre-set maximum temperature limiter



Ergonomic: solid lever is easy to grip



Comfort: optimum drop height and spout projection

TECHNICAL CHARACTERISTICS

Mechanical mixer for sinks or troughs - Ref. 2510T

Connector	F3/8"
Height	177mm
Drop height	155mm
Spout length	230mm
Flow rate	9 lpm at 3 bar
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	ACS (1) (1)
Warranty	30 S WARRANTY
Repairability	50 g

