

# TEMPOMATIC MIX 4

## electronic mixer

Ref. 49000615

Integrated batteries, stopcocks Ø 15mm

### DESCRIPTION

**TEMPOMATIC MIX 4 electronic mixer - Ref. 49000615**

Deck-mounted electronic basin mixer:  
 Battery-operated with integrated 123 6V Lithium batteries.  
 Reduced stagnation solenoid valve and electronic unit integrated into the body of the mixer.  
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.  
 Scale-resistant flow straightener.  
 Duty flush (~60 seconds every 24 hours after last use).  
 Presence detection sensor at the end of the spout optimises detection.  
 Chrome-plated stainless steel body.  
 Cap fixed in place by two concealed screws.  
 PEX flexibles Ø 15mm for compression fittings with stopcocks, filters and non-return valves.  
 Fixing reinforced by 2 stainless steel rods.  
 Anti-blocking security.  
 Side temperature control with adjustable maximum temperature limiter.  
 Suitable for people with reduced mobility.  
 30-year warranty.

### TECHNICAL CHARACTERISTICS

**TEMPOMATIC MIX 4 electronic mixer - Ref. 49000615**

|               |                                                                                     |
|---------------|-------------------------------------------------------------------------------------|
| Supply        | 6V batteries                                                                        |
| Connector     | M½" Ø 15mm                                                                          |
| Technology    | Electronic                                                                          |
| Drop height   | 70mm                                                                                |
| Spout length  | 105mm                                                                               |
| Flow rate     | 3 lpm                                                                               |
| Norms         |  |
| Warranty      |  |
| Repairability |  |



### ADVANTAGES

-  Exceptional water savings: 90%
-  Hygiene: no manual contact
-  Batteries integrated in mixer body
-  Integrated solenoid valve

