

SECURITHERM shower panel

Ref. 792305

Thermostatic time flow





DESCRIPTION

SECURITHERM shower panel - Ref. 792305

Thermostatic time flow shower panel:
Anodised aluminium shower panel for wall-mounted, exposed installation.
With top inlet via in-line stopcocks M1/2".
SECURITHERM thermostatic mixer.
Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.
Anti-scalding failsafe: automatic shut-off if cold water fails.
Anti-cold showers function: automatic shut-off if hot water fails.
Thermal shocks are possible.
Soft-touch operation.
Time flow ~30 seconds.
Flow rate set at 6 lpm at 3 bar.
Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.
With soap dish.
Concealed fixings.
Filters and non-return valves.
Suitable for people with reduced mobility.
30-year warranty.





TECHNICAL CHARACTERISTICS

SECURITHERM shower panel - Ref. 792305

Connector	M1/2"
Technology	Time flow
Height	1050mm
Depth	65mm
Width	210mm
Flow rate	6 lpm
Temperature limiter	Thermostatic
Finish	Aluminium
Norms	  
Warranty	



ADVANTAGES

-  Thermostatic temperature regulation
-  Instant shut-off if cold water fails
-  80% water savings
-  Aluminium panel, brass controls

