TEMPOMATIC electronic shower kit

Ref. 452159

Electronic

DESCRIPTION

TEMPOMATIC electronic shower kit - Ref. 452159

Cross wall electronic shower kit:
TEMPOMATIC electronic valve for mixed water supply.
For walls ≤ 155mm.
Power supply by electronic unit with solenoid valve 1/2".
230/12V transformer.
2 operation modes:
- Automatic activation via presence detection.
- Voluntary ON/OFF activation by passing the hand in front of sensor ~10 cm.
Duty flush (~60 seconds every 24 hours after the last use).
Adjustable time flow from 30 to 60 seconds.
Flow rate set at 6 lpm at 3 bar.
Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.
Chrome-plated solid brass.
Wall plate flush to the wall.
Threaded rods can be cut-to-size.
Electronic shower kit suitable for people with reduced mobility.
30-year warranty.

ADVANTAGES

- 230/12V
- Total hygiene: no manual contact
- Anti-bacterial duty flush
- 2 operation modes

TECHNICAL CHARACTERISTICS

TEMPOMATIC electronic shower kit - Ref. 452159

Supply	230/12V mains supply
Connector	½"
Technology	Electronic
Length	155mm
Flow rate	6 lpm
Norms	ACS CE
Warranty	30 YEAR WARRANTY