

TEMPOMATIC shower panel

Ref. 452300

Electronic

DESCRIPTION

TEMPOMATIC shower panel - Ref. 452300

Electronic shower panel:
Anodised aluminium shower panel for wall-mounted, exposed installation.
With top inlet via in-line stopcock, M1/2".
TEMPOMATIC electronic mixer for mixed water supply.
Battery-operated with 223 6V Lithium battery.
Infrared presence detection. Shower starts when hand is at 4cm from the sensor.
Shuts off on demand or automatically after ~60 seconds.
Duty flush (~60 seconds every 24 hours after the last use).
Flow rate set at 6 lpm at 3 bar.
Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.
Concealed fixings.
Filter.
Suitable for people with reduced mobility.
30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC shower panel - Ref. 452300

Supply	6V battery
Connector	M1/2"
Technology	Electronic
Height	1050mm
Depth	65mm
Width	210mm
Flow rate	6 lpm
Finish	Aluminium
Norms	ACS  
Warranty	



ADVANTAGES



Total hygiene: operate without manual contact



Automatic flush anti-bacterial proliferation

