TEMPOMIX time flow shower mixer

Ref. 790925

Single control time flow



DESCRIPTION

TEMPOMIX time flow shower mixer - Ref. 790925

Recessed time flow shower kit:

Chrome-plated Ø 195mm wall plate.

Standard recessing housing.

Recessing depth adjustable from 28 - 43mm.

TEMPOMIX ¾" single control mixer.

Ligature-resistant collar.

Temperature control and operation via the push-button.

Maximum temperature limiter (can be adjusted by the installer).

Time flow ~30 seconds, soft-touch operation.

Flow rate 12 lpm at 3 bar.

 $M\frac{1}{2}$ " connectors for Ø 15mm copper tubes.

Integrated non-return valves and filters.

Chrome-plated metal control.

30-year warranty.

As this model does not come with waterproof recessing housing the installer must ensure the watertightness of the recessing area and allow for run-off of leaks and condensation (see installation guide).

TECHNICAL CHARACTERISTICS

TEMPOMIX time flow shower mixer - Ref. 790925

Connector	M1/2'' Ø 15mm
Technology	Time flow
Flow rate	12 lpm
Norms	ACS (E
Warranty	30 g WARRANTY

ADVANTAGES



Recessed wall installation



Time flow system tested to 500,000+ operations



Soft-touch operation

