

TEMPOMIX 3 time flow shower kit

Ref. 794450

Time flow single control

DESCRIPTION

TEMPOMIX 3 time flow shower kit - Ref. 794450

Exposed time flow shower kit:
TEMPOMIX 3 single control mixer ¾", top outlet.
For wall-mounted, exposed installation.
Temperature control and operation via the push-button.
Maximum temperature limiter (can be adjusted by the installer).
Soft-touch operation.
Time flow ~30 seconds.
Flow rate 6 lpm at 3 bar, can be adjusted, rain-effect spray.
Chrome-plated and tamperproof TONIC JET shower head.
Chrome-plated brass.
Integrated filters and non-return valves.
Chrome-plated metal push-button.
Shower column Ø 16mm with reinforced collar (fixing plate and screws included).
M½" offset connectors for 130 - 170mm centres.
Suitable for people with reduced mobility.
30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMIX 3 time flow shower kit - Ref. 794450

Connector	M½"
Technology	Time flow
Height	1,010mm
Width	150mm
Flow rate	6 lpm
Norms	  
Warranty	



ADVANTAGES



Exceptional water savings: 80%



Soft-touch operation



Time flow system tested to over 500,000 operations

