## DELABIE

# Shower kit with thermostatic mixer

Ref. H9769SKIT

Shower kit with thermostatic mixer with no non-return valves

#### DESCRIPTION

#### Shower kit with thermostatic mixer - Ref. H9769SKIT

Shower riser rail with dual control thermostatic shower mixer. Shower kit with SECURITHERM thermostatic shower mixer. Thermostatic mixer with no non-return valves on the inlets (reduced bacterial proliferation).

No risk of cross flow between hot and cold water.

Mixer with anti-scalding failsafe: shuts off automatically if cold water supply fails.

Prevents cold showers: shuts off automatically if hot water supply fails. Securitouch thermal insulation prevents burns.

Scale-resistant thermostatic cartridge for temperature adjustment.

Temperature control up to 43°C.

Double temperature limiter: 1st limiter set at 41°C can be overridden, 2nd limiter set at 43°C.

Thermal shocks are possible without removing the control knob or shutting off the cold water supply.

Flow rate limited to 9 lpm at 3 bar.

Chrome-plated brass body with ergonomic controls.

M<sup>1</sup>/<sub>2</sub>" shower outlet.

 $F\%^{\prime\prime}$  inlets with integrated filters.

Mixer supplied with offset standard wall connectors M<sup>1</sup>/<sub>2</sub>" M<sup>3</sup>/<sub>4</sub>".

• Sliding shower head holder (ref. 813) on a chrome-plated riser rail (ref. 821)

with soap dish and flexible hose (ref. 836T1).

• Shower head retaining collar (ref. 830).

Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Mixer suitable for people with reduced mobility. Shower kit with 30-year warranty.

## **TECHNICAL CHARACTERISTICS**

#### Shower kit with thermostatic mixer - Ref. H9769SKIT

Connector	M1/2"
Technology	SECURITHERM Securitouch thermostatic mixer, no non-return valves
Depth	84mm
Length	260mm
Flow rate	9 lpm at 3 bar
Temperature limiter	Yes
Finish	Chrome-plated brass



### ADVANTAGES



SECURITHERM: Anti-scalding safety




Maximum hygiene: no non-return valves



Securitouch thermal insulation prevents burns



Thermostatic: total temperature stability



# DELABIE

Norms	ACS
Warranty	30 KA