

# SECURITHERM BIOCLIP

## thermostatic basin mixer

Ref. H9605610

Single hole sequential thermostatic mixer H. 95mm L. 120mm



### DESCRIPTION


**SECURITHERM BIOCLIP thermostatic basin mixer - Ref. H9605610**

Deck-mounted SECURITHERM thermostatic basin mixer.  
 Sequential thermostatic mixer: opens and closes with cold water.  
 No risk of cross flow between the hot and cold water.  
 No non-return valves on the inlets.  
 BIOCLIP: mixer can be easily removed for cleaning and disinfection.  
 Anti-scalding failsafe: shuts off automatically if cold or hot water supply fails.  
 Securitouch thermal insulation prevents burns.  
 Single hole mixer with curved spout, H. 95mm L. 120mm, fitted with a hygienic flow straightener, no build-up of impurities and withstands thermal shocks.  
 Scale-resistant sequential thermostatic cartridge for single control adjustment of flow rate and temperature.  
 Temperature adjusts from cold water up to 40°C with maximum temperature limiter set at 40°C.  
 Tested without water to comply with NHS requirements. No pre-set temperature.  
 Thermal and chemical shocks are possible.  
 Spout and body with smooth interior and low water volume.  
 Flow rate limited to 5 lpm at 3 bar.  
 No manual contact thanks to Hygiene control lever L. 146mm.  
 Without pop-up waste.  
 Supplied with copper tails and chrome-plated brass stopcocks.  
 Fixing reinforced via 2 stainless steel rods.  
 Ideal for healthcare facilities, retirement and care homes, hospitals and clinics.  
 Mixer suitable for people with reduced mobility.  
 Mixer with 30-year warranty.  
 Also available with PEX flexibles.

### TECHNICAL CHARACTERISTICS

**SECURITHERM BIOCLIP thermostatic basin mixer - Ref. H9605610**

Connector	M1/2", Ø 15mm
Technology	SECURITHERM BIOCLIP sequential thermostatic mixer
Drop height	95mm
Spout length	120mm
Flow rate	5 lpm at 3 bar
Temperature limiter	Yes
Finish	Chrome-plated brass



---

Norms



---

Warranty



---

Repairability

