## SECURITHERM BIOCLIP thermostatic basin mixer

Ref. H9605610L

Single hole, sequential thermostatic mixer H. 95mm L. 120mm



SECURITHERM BIOCLIP thermostatic basin mixer - Ref. H9605610L

Deck-mounted SECURITHERM thermostatic basin mixer.

Sequential thermostatic mixer: opens and closes with cold water.

No risk of cross flow between the hot and cold water.

No non-return valves on the inlets.

BIOCLIP: can be easily removed for cleaning and disinfection.

Anti-scalding failsafe: shuts off automatically if the cold or hot water supply

Securitouch thermal insulation prevents burns.

Single hole mixer with straight spout, H. 95mm L. 120mm, fitted with a hygienic flow straightener, with no build-up of impurities and withstands thermal shocks

Scale-resistant sequential thermostatic cartridge for single control adjustment of flow rate and temperature.

Adjustable temperature from cold water up to 40°C with maximum temperature limiter set at 40°C.

Tested without water to comply with NHS requirements. No pre-set temperature.

Thermal and chemical shocks are possible.

Spout and body with smooth interiors and low water volume.

Flow rate limited to 5 lpm at 3 bar.

No manual contact thanks to Hygiene control lever L. 100mm.

Without pop-up waste.

Supplied with copper tails and chrome-plated brass stopcocks.

Fixing reinforced via 2 stainless steel rods.

Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Mixer suitable for people with reduced mobility.

30-year warranty.

Also available with PEX flexibles.

## TECHNICAL CHARACTERISTICS

SECURITHERM BIOCLIP thermostatic basin mixer - Ref. H9605610L

Connector	M1/2" Ø 15mm
Technology	SECURITHERM BIOCLIP sequential Securitouch
Drop height	95mm
Spout length	120mm
Flow rate	5 lpm at 3 bar
Temperature limiter	Yes
Finish	Chrome-plated brass



## **ADVANTAGES**



Maximum hygiene: no non-return




Hygiene: can be removed for internal cleaning



SECURITHERM: anti-scalding safety



Sequential: opens/closes with cold water



## **DELABIE**

Norms	<b>₩RAS</b>
Warranty	30 S
Repairability	50 B

© DELABIE https://www.delabie.co.uk