## DELABIE

# SECURITHERM thermostatic basin mixer

Ref. H9600610L

Single hole sequential thermostatic mixer, H. 95mm L. 120mm

### DESCRIPTION

#### SECURITHERM thermostatic basin mixer - Ref. H9600610L

Deck-mounted thermostatic SECURITHERM basin mixer. Sequential thermostatic mixer: opens and closes with cold water. No risk of cross flow between hot and cold water. No non-return valve on the inlets. Anti-scalding failsafe: shuts off automatically if cold or hot water supply fails. Securitouch thermal insulation prevents burns. Single hole mixer with curved spout H. 95mm L. 120mm fitted with a hygienic flow straightener, no build-up of impurities and withstands thermal shocks. Scale-resistant sequential thermostatic cartridge for single control of flow rate and temperature. Temperature can be adjusted from cold water up to 40°C with maximum temperature limiter set at 40°C. Thermal and chemical shocks are possible. Body and spout with smooth interiors and low water volume. Flow rate limited to 5 lpm at 3 bar. No manual contact thanks to Hygiene control lever L. 146mm. Without pop-up waste. Supplied with copper tails and stopcocks in chrome-plated brass. Reinforced fixing via 2 stainless steel rods. Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Mixer suitable for people with reduced mobility.

30-year warranty.

Also available with PEX flexibles.

### **TECHNICAL CHARACTERISTICS**

#### SECURITHERM thermostatic basin mixer - Ref. H9600610L

Connector	M1/2'' Ø 15mm
Technology	SECURITHERM Securitouch sequential mixer
Drop height	95mm
Spout length	120mm
Flow rate	5 lpm
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	uwras 🌋
Warranty	



## ADVANTAGES



Sequential: opens/closes with cold water




Maximum hygiene: no non-return valves



SECURITHERM: optimal anti-scalding safety



Securitouch thermal insulation prevents burns



# DELABIE

Repairability

