

## TEMPOMATIC MIX 4 electronic mixer

Ref. 49000015

Recessed mains supply, stopcocks Ø 15mm





### DESCRIPTION

TEMPOMATIC MIX 4 electronic mixer - Ref. 49000015





Deck-mounted electronic basin mixer:  
230/6V recessed mains supply.  
Reduced stagnation solenoid valve and electronic unit integrated into the body of the mixer.  
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.  
Scale-resistant flow straightener.  
Duty flush (~60 seconds every 24 hours after last use).  
Presence detection sensor at the end of the spout optimises detection.  
Chrome-plated stainless steel body.  
Cap fixed in place by two concealed screws.  
PEX flexibles Ø 15mm for compression fittings with stopcocks, filters and non-return valves.  
Fixing reinforced by 2 stainless steel rods.  
Anti-blocking security.  
Side temperature control with standard lever and adjustable maximum temperature limiter.  
Suitable for people with reduced mobility.  
30-year warranty.

### TECHNICAL CHARACTERISTICS

TEMPOMATIC MIX 4 electronic mixer - Ref. 49000015

|              |   |
|--------------|---|
| Supply       | 230/6V mains supply (recessed)  |
| Connector    | M1/2" Ø 15mm  |
| Technology   | Electronic  |
| Drop height  | 70mm  |
| Spout length | 105mm   |
| Flow rate    | 3 lpm   |
| Norms        |  |
| Warranty     |  |

### ADVANTAGES

-  Exceptional water savings: 90%
-  Hygiene: no manual contact
-  Recessed mains supply
-  Integrated solenoid valve

