TEMPOMATIC MIX 4 electronic mixer

Ref. 49000015

Recessed mains supply, stopcocks Ø 15mm



ADVANTAGES



Total hygiene: no manual contact



Water savings up to 90%



Recessed mains supply



Duty flush limits bacterial proliferation

DESCRIPTION

TEMPOMATIC MIX 4 electronic mixer - Ref. 49000015

Deck-mounted electronic basin mixer:

230/6V recessed mains supply.

Reduced stagnation solenoid valve and electronic unit integrated into the body of the mixer.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.

Scale-resistant flow straightener.

Duty flush (~60 seconds every 24 hours after last use).

Active, infrared presence detection, sensor at the end of the spout optimises detection.

Chrome-plated stainless steel body.

Cap fixed in place by two concealed screws.

PEX flexibles \emptyset 15mm for compression fittings with stopcocks, filters and non-return valves.

Fixing reinforced by 2 stainless steel rods.

Anti-blocking security.

Side temperature control with standard lever and adjustable maximum temperature limiter.


Suitable for people with reduced mobility.

30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC MIX 4 electronic mixer - Ref. 49000015

230/6V mains supply (recessed)
M1/2" Ø 15mm
Electronic
70mm
105mm
3 lpm
CE
30 %



© DELABIE