

## TEMPOMATIC 4 electronic tap

Ref. 44000015

Recessed mains supply, 15mm stopcock



### DESCRIPTION

TEMPOMATIC 4 electronic tap - Ref. 44000015

Deck-mounted electronic basin tap:  
 230/6V recessed mains supply.  
 Reduced stagnation solenoid valve and electronic unit integrated into the body of the tap.  
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.  
 Scale-resistant flow straightener.  
 Duty flush (~60 sec. every 24h after last use).  
 Presence detection sensor at the end of the spout optimises detection.  
 Chrome-plated stainless steel body.  
 Cap fixed in place by two concealed screws.  
 PEX flexible with stopcock, filter and Ø 15mm conical inlet.  
 Fixing reinforced by 2 stainless steel rods.  
 Anti-blocking security.  
 Suitable for people with reduced mobility.  
 30-year warranty.

### TECHNICAL CHARACTERISTICS

TEMPOMATIC 4 electronic tap - Ref. 44000015

Supply	230/6V (recessed mains supply)
Connector	M $\frac{1}{2}$ " Ø 15mm
Technology	Electronic
Drop height	70mm
Spout length	105mm
Flow rate	3 lpm
Norms	
Warranty	

### ADVANTAGES

-  Proven water savings: 90%
-  Hygiene: no manual contact
-  Recessed mains supply
-  Integrated solenoid valve

