

BINOPTIC electronic tap

Ref. 37801515

Mains supply, Ø 15mm compression fittings



DESCRIPTION

BINOPTIC electronic tap - Ref. 37801515

Deck-mounted electronic basin tap:
Independent IP65 electronic control unit.
230/12V mains supply with transformer.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.
Scale-resistant flow straightener.
Adjustable duty flush (pre-set flush ~60 seconds every 24hr after last use).
Active, infrared movement detection, sensor at the end of the spout optimises detection.
Chrome-plated solid brass body.
PEX flexible with filter, solenoid valve and Ø 15mm compression fittings.
Fixing reinforced by 2 stainless steel rods.
Anti-blocking security.
Spout with a smooth interior and low volume of water (limits bacterial niches).
Suitable for people with reduced mobility.
30-year warranty.

TECHNICAL CHARACTERISTICS

BINOPTIC electronic tap - Ref. 37801515

Supply	230/12V mains supply
Connector	M1/2" Ø 15mm
Technology	Electronic
Drop height	90mm
Spout length	125mm
Flow rate	3 lpm
Norms	 
Warranty	

ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Duty flush limits bacterial proliferation



LED diagnostic aid

