

## BINOPTIC electronic tap

Ref. 47801515

Battery-operated, Ø 15mm conical inlet



### DESCRIPTION

**BINOPTIC electronic tap - Ref. 47801515**

Deck-mounted electronic basin tap:  
Independent IP65 electronic control unit.  
123 6V Lithium battery.  
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.  
Scale-resistant flow straightener.  
Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).  
Active, infrared movement detection, sensor at the end of the spout optimises detection.  
Chrome-plated solid brass body.  
PEX flexible with filter, solenoid valve and Ø 15mm conical inlet.  
Fixing reinforced by 2 stainless steel rods.  
Anti-blocking security.  
Spout with a smooth interior and low volume of water (limits bacterial niches).  
Suitable for people with reduced mobility.  
30-year warranty.

### TECHNICAL CHARACTERISTICS

**BINOPTIC electronic tap - Ref. 47801515**

Supply	6V battery
Connector	M1/2" Ø 15mm
Technology	Electronic
Drop height	90mm
Spout length	125mm
Flow rate	3 lpm
Warranty	

### ADVANTAGES



Total hygiene: no manual contact



90% water savings



6V batteries



Duty flush limits bacterial proliferation

