

# TEMPOMATIC MIX PRO

## electronic mixer

Ref. 49525315

Mains supply, Ø 15mm conical inlets



### DESCRIPTION

**TEMPOMATIC MIX PRO electronic mixer - Ref. 49525315**

Deck-mounted electronic basin mixer:  
Independent IP65 electronic control unit.  
230/12V mains supply with transformer.  
Flow rate pre-set at 4 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.  
Scale-resistant flow straightener.  
Solenoid valves are upstream of the mixing chamber.  
Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).  
Shock-resistant infrared presence detection sensor.  
Chrome-plated solid brass body with fixing reinforced by 2 stainless steel rods.  
PEX flexibles with filters and solenoid valves Ø 15mm for compression fitting.  
360° swivelling spout with smooth interior (reduces bacterial development).  
Removable spout for cleaning.  
Anti-blocking security.  
Side temperature control with adjustable maximum temperature limiter and long ergonomic lever.  
30-year warranty.  
Two shut-off options:  
Standard mode: timed flow with automatic shut-off  
ON/OFF mode: user shuts off voluntarily or automatic shut-off after 30 minutes of flow. Thermal shocks are possible.

### TECHNICAL CHARACTERISTICS

**TEMPOMATIC MIX PRO electronic mixer - Ref. 49525315**

Supply	230/12V mains supply
Connector	M1/2" Ø 15mm
Technology	Electronic
Drop height	310mm
Spout length	200mm
Flow rate	4 lpm
Norms	CE
Warranty	30 YEARS WARRANTY

### ADVANTAGES



Total hygiene: no manual contact



85% water savings



Independent IP65 electronic control unit



Anti-bacterial proliferation duty flush

