TEMPOMATIC PRO electronic tap

Ref. 44525715

Battery-operated, Ø 15mm conical inlet



DESCRIPTION

TEMPOMATIC PRO electronic tap - Ref. 44525715

Deck-mounted electronic basin tap:

Independent IP65 electronic control unit.

Battery-operated with 123 6V Lithium batteries.

Flow rate pre-set at 4 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.

Scale-resistant flow straightener.

Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use). Shock-resistant infrared presence detection sensor.

Chrome-plated solid brass body with fixing reinforced by 2 stainless steel rods. PEX flexible with filter and solenoid valve Ø 15mm for compression fittings. 360° swivelling spout with smooth interior (reduces bacterial development). Removable spout for cleaning.

Anti-blocking security.

Suitable for people with reduced mobility.

30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC PRO electronic tap - Ref. 44525715

Supply	6V battery
Connector	M1/2" Ø 15mm
Technology	Electronic
Drop height	310mm
Spout length	200mm
Flow rate	3 lpm
Warranty	30 g

ADVANTAGES



Total hygiene: no manual contact




85% water savings



Independent IP65 electronic control unit



Duty flush limits bacterial proliferation



© DELABIE https://www.delabie.co.uk