

# TEMPOSOFT MIX 2 time flow mixer

Ref. 74250015

Soft-touch operation, Ø 15mm stopcocks

## DESCRIPTION

TEMPOSOFT MIX 2 time flow mixer - Ref. 74250015

Deck-mounted time flow basin mixer:  
Soft-touch operation.  
Time flow ~7 seconds.  
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.  
Tamperproof scale-resistant flow straightener.  
Chrome-plated solid brass body.  
PEX flexibles with stopcocks, filters, non-return valves and Ø 15mm conical inlets.  
Fixing reinforced by 2 stainless steel rods.  
Side temperature control with standard lever and maximum temperature limiter.  
Suitable for people with reduced mobility.  
30-year warranty.

## TECHNICAL CHARACTERISTICS

TEMPOSOFT MIX 2 time flow mixer - Ref. 74250015

|               |                                                                                     |
|---------------|-------------------------------------------------------------------------------------|
| Connector     | M1/2" Ø 15mm                                                                        |
| Technology    | Time flow                                                                           |
| Drop height   | 85mm                                                                                |
| Spout length  | 100mm                                                                               |
| Flow rate     | 3 lpm                                                                               |
| Norms         |  |
| Warranty      |  |
| Repairability |  |



## ADVANTAGES



Exceptional water savings: 85%



Chrome-plated solid brass body



Soft-touch operation



Sleek design

