

# Sequential thermostatic shower mixer

Ref. H963015

SECURITHERM mixer with no non-return valve, bottom outlet



## DESCRIPTION

Sequential thermostatic shower mixer - Ref. H963015

SECURITHERM thermostatic sequential shower mixer.  
Thermostatic sequential mixer: opens and closes with cold water.  
Mixer with no non-return valves on the inlets (reduces bacterial proliferation).  
No risk of cross flow between hot and cold water.  
Sequential mixer with anti-scalding failsafe: shuts off immediately if cold water supply fails.  
Prevents cold showers: shuts off immediately if hot water supply fails  
Securitouch thermal insulation prevents burns.  
Scale-resistant thermostatic sequential cartridge adjusts the flow rate and the temperature.  
Temperature can be adjusted from cold water to 39°C with maximum temperature limiter set at 39°C.  
Thermal shocks are possible.  
Body with smooth interior and low water volume (reduces niches where bacteria can develop).  
Flow rate regulated at 9 lpm.  
Chrome-plated brass body and Hygiene control lever L. 100mm.  
M1/2" bottom shower outlet.  
Wall-mounted mixer with M1/2" M3/4" inline STOP/CHECK.  
Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.  
Sequential mixer suitable for people with reduced mobility.  
Shower mixer with 30-year warranty.

## ADVANTAGES



Sequential, opens/closes with cold water



No non-return valves on the inlets





SECURITHERM: optimal anti-scalding safety



Thermostatic: complete temperature stability

## TECHNICAL CHARACTERISTICS

Sequential thermostatic shower mixer - Ref. H963015

Connector	M1/2"
Technology	SECURITHERM Securitouch sequential thermostatic mixer
Length	184mm
Flow rate	9 lpm
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	
Warranty	
Repairability	