

TEMPOMATIC tap with BIOCLIP removable spout

Ref. 20804T215

Electronic wall-mounted tap with mains supply





DESCRIPTION

TEMPOMATIC tap with BIOCLIP removable spout - Ref. 20804T215





Independent IP65 electronic control unit.
 230/12V mains supply with transformer.
 Supplied with 2 removable BIOCLIP stainless steel spouts
 L. 190mm Ø 28mm for continuous use during cleaning/disinfection.
 Can be replaced with a BIOFIL filter or disposable Hostaform® spout.
 Base and spout with smooth interiors (reduces bacterial development).
 Adjustable duty flush (pre-set at ~60 seconds every 24 hours after last use).
 Flow rate limited to 4 lpm at 3 bar.
 Separate sensor for mounting on panels.
 Solenoid valve Ø 15mm for compression fittings with integrated filter.
 Shock-resistant infrared presence detection sensor.
 Ø 60mm chrome-plated brass base.
 Anti-blocking security.
 Recommended installation height: 110 - 200mm above the basin surface.
 Suitable for people with reduced mobility.
 10-year warranty.
 Two shut-off options:
 - Standard mode: timed flow with automatic shut-off.
 - ON/OFF mode: user shuts off flow voluntarily or automatic shut-off after 30 minutes of flow.
 Thermal shocks are possible.

TECHNICAL CHARACTERISTICS

TEMPOMATIC tap with BIOCLIP removable spout - Ref. 20804T215

Connector	Ø 15mm
Technology	Electronic
Depth	190mm
Length	129mm
Spout length	188mm
Flow rate	4 lpm
Finish	Chrome-plated brass
Norms	
Warranty	

ADVANTAGES

-  Automatic duty flush limits bacterial development
-  Hygiene: spout can be removed and descaled inside
-  Hygiene: smooth interior reduces bacteria
-  Infrared detection with no manual contact

