

KOMPACT washbasin and floor-standing WC combination

Ref. 160700

Polished satin 304 stainless steel, Wall mount, Floor mount WC on LHS



DESCRIPTION

KOMPACT washbasin and floor-standing WC combination - Ref. 160700

Combination unit: washbasin and floor-standing WC pan on left sidewith recessed toilet roll holder.
 Wall-mounted installation with 3 access panels, 2 on the sides and 1 on the top with theft prevention TORX security screws.
 Bacteriostatic 304 stainless steel.
 Polished satin finish
 Stainless steel unit thickness: 2mm.
 Rounded corners and edges for improved safety.
 Smooth surface for easy cleaning.
 Suitable for prisons, police stations, etc.
 WC pan is completely welded to washbasin, no screws: makes cleaning easier and prevents concealment of objects.
 Washbasin equipped with time flow tap: stainless steel tamperproof push-button and anti-blocking system, 7 second time flow, M $\frac{1}{2}$ ".
 WC equipped with time flow flush valve, 7 second time flow, M $\frac{3}{4}$ ".
 Water inlet: washbasin M $\frac{1}{2}$ ", WC M $\frac{3}{4}$ ".
 Recessed horizontal water outlet: Ø 100mm.
 Supplied with washbasin siphon.
 Easy to install: only one water outlet for both washbasin and WC, water inlet and outlet already connected.
 Weight: 36kg.
 [Formerly ref: 0610030007]

TECHNICAL CHARACTERISTICS

KOMPACT washbasin and floor-standing WC combination - Ref. 160700

Height	1000mm
Length	725mm
Width	735mm
Thickness	2mm
Finish	304 polished satin stainless steel
Norms	ACS 
Warranty	

ADVANTAGES



Bacteriostatic 304 stainless steel



Suitable for secure sector

