

# SECURITHERM shower panel

Ref. 792320

Thermostatic time flow dual control

## DESCRIPTION

**SECURITHERM shower panel - Ref. 792320**

SECURITHERM dual control thermostatic time flow shower panel:  
Anodised aluminium shower panel for wall-mounted, exposed installation.  
With top inlet via in-line stopcocks, M $\frac{1}{2}$ ".  
SECURITHERM thermostatic shower mixer.  
Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.  
Anti-scalding failsafe: automatic shut-off if cold water fails.  
Anti-cold showers function: automatic shut-off if hot water fails.  
Thermal shocks are possible.  
Soft-touch operation.  
Chrome-plated, tamperproof, scale-resistant, fixed, ROUND shower head with automatic flow rate regulation at 6 lpm at 3 bar.  
Handset with removable flexible via push-fit rapid STOP connector and wall support supplied.  
2x ~30-second time flow valves to control ROUND shower head and handset on flexible hose.  
Concealed fixings.  
Filters and non-return valves.  
Shower panel suitable for people with reduced mobility.  
30-year warranty.

## TECHNICAL CHARACTERISTICS

**SECURITHERM shower panel - Ref. 792320**

|                     |                                                                                                                                                                                                                                                                                                                                                 |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connector           | M1/2"                                                                                                                                                                                                                                                                                                                                           |
| Technology          | Time flow                                                                                                                                                                                                                                                                                                                                       |
| Height              | 1050mm                                                                                                                                                                                                                                                                                                                                          |
| Depth               | 65mm                                                                                                                                                                                                                                                                                                                                            |
| Width               | 210mm                                                                                                                                                                                                                                                                                                                                           |
| Flow rate           | 6 lpm                                                                                                                                                                                                                                                                                                                                           |
| Temperature limiter | thermostatic                                                                                                                                                                                                                                                                                                                                    |
| Finish              | Aluminium                                                                                                                                                                                                                                                                                                                                       |
| Norms               |     |
| Warranty            |                                                                                                                                                                                                                                                              |



## ADVANTAGES

-  Thermostatic temperature regulation
-  Immediate shut-off if cold water fails
-  80% water savings
-  Aluminium body, brass controls

