

# SECURITHERM shower panel

Ref. 792304CF

Time flow thermostatic



## DESCRIPTION

**SECURITHERM shower panel - Ref. 792304CF**

Thermostatic time flow shower panel:  
Large model satin stainless steel shower panel for wall mounted, exposed installation.  
Top inlet via in-line stopcocks M $\frac{1}{2}$ ".  
SECURITHERM thermostatic shower mixer.  
Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.  
Anti-scalding safety: automatic shut-off if cold or hot water supply fails.  
Thermal shocks are possible.  
Soft-touch operation.  
Time flow ~30 seconds.  
Flow rate 6 lpm at 3 bar.  
Chrome-plated, tamperproof, scale-resistant, fixed, ROUND shower head with automatic flow rate regulation.  
Integrated soap dish.  
Concealed fixings.  
Filters and non-return valves.  
Shower panel suitable for people with reduced mobility.  
30-year warranty.

## TECHNICAL CHARACTERISTICS

**SECURITHERM shower panel - Ref. 792304CF**

Connector	M $\frac{1}{2}$ "
Technology	Time flow
Height	1220mm
Depth	100mm
Width	250mm
Flow rate	10 lpm
Temperature limiter	Thermostatic
Finish	Stainless steel
Norms	ACS
Warranty	

## ADVANTAGES



Thermostatic temperature regulation



Immediate shut-off if cold water fails



80% water savings



Stainless steel sheath, brass controls

