

# SECURITHERM time flow shower panel

Ref. 792303CF

Time flow thermostatic


## DESCRIPTION

**SECURITHERM time flow shower panel - Ref. 792303CF**

Thermostatic time flow shower panel:  
 Large model satin stainless steel shower panel for wall mounted, exposed installation.  
 Top inlet via in-line stopcocks M $\frac{1}{2}$ ".  
 Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.  
 Anti-scalding failsafe: automatic shut-off if cold or hot water supply fails.  
 Anti-cold showers function: automatic shut-off if hot water fails.  
 Thermal shocks are possible.  
 Soft-touch operation.  
 Time flow ~30 seconds.  
 Flow rate 6 lpm at 3 bar.  
 Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.  
 Concealed fixings.  
 Filters and non-return valves.  
 Suitable for people with reduced mobility.  
 30-year warranty.





## TECHNICAL CHARACTERISTICS

**SECURITHERM time flow shower panel - Ref. 792303CF**

|                     |   |
|---------------------|---|
| Connector           | M $\frac{1}{2}$ "   |
| Technology          | Time flow   |
| Height              | 1,220mm   |
| Depth               | 100mm   |
| Width               | 250mm   |
| Flow rate           | 6 lpm   |
| Temperature limiter | Thermostatic  |
| Finish              | Stainless steel   |
| Norms               | ACS   |
| Warranty            |  |



## ADVANTAGES

-  Thermostatic temperature regulation
-  Immediate shut-off if cold water fails
-  80% water savings
-  Stainless steel sheath, brass controls

