

SECURITHERM time flow shower panel

Ref. 792313CF

Time flow thermostatic, comfort 10 lpm

DESCRIPTION

SECURITHERM time flow shower panel - Ref. 792313CF

Thermostatic time flow shower panel:
Large model satin stainless steel shower panel for wall mounted, exposed installation.
Concealed inlet via flexibles M $\frac{1}{2}$ ".
SECURITHERM thermostatic shower mixer.
Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.
Anti-scalding failsafe: automatic shut-off if cold or hot water supply fails.
Anti-cold showers function: automatic shut-off if hot water fails.
Thermal shocks are possible.
Soft-touch operation.
Chrome-plated, tamperproof, scale-resistant, fixed, ROUND shower head with automatic flow rate regulation.
Time flow ~30 seconds.
Flow rate 10 lpm at 3 bar.
M $\frac{1}{2}$ " stopcocks.
Concealed fixings.
Filters and non-return valves.
Shower panel suitable for people with reduced mobility.
30-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM time flow shower panel - Ref. 792313CF

Connector	M $\frac{1}{2}$ "
Technology	Time flow
Height	1,220mm
Depth	100mm
Width	250mm
Flow rate	10 lpm
Temperature limiter	Thermostatic
Finish	Stainless steel
Norms	ACS
Warranty	



ADVANTAGES



Thermostatic temperature regulation



Instant shut-off if cold water fails



Stainless steel sheath, brass controls

