

SECURITHERM dual control shower panel

Ref. 792344CF

Mechanical thermostatic dual control, comfort 10 lpm


DESCRIPTION

SECURITHERM dual control shower panel - Ref. 792344CF

Dual control thermostatic shower panel:
Large model satin stainless steel shower panel for wall mounted, exposed installation.
Top inlet via inline stopcocks M $\frac{1}{2}$ ".
SECURITHERM thermostatic shower mixer.
Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.
Anti-scalding failsafe: automatic shut-off if cold or hot water supply fails.
Chrome-plated, tamperproof, scale-resistant, fix, ROUND shower head with automatic flow rate regulation at 10 lpm at 3 bar.
Handset with removable flexible via rapid push-fit STOP connector, wall support supplied.
2 non-time flow valves control fixed ROUND shower head and handset with flexible hose.
Thermal shocks are possible.
Concealed fixings.
Filters and non-return valves.
Shower panel suitable for people with reduced mobility.
30-year warranty.





TECHNICAL CHARACTERISTICS

SECURITHERM dual control shower panel - Ref. 792344CF

Connector	M $\frac{1}{2}$ "
Technology	Non-Time flow
Height	1,220mm
Depth	100mm
Width	250mm
Flow rate	10 lpm
Temperature limiter	Thermostatic
Finish	Stainless steel
Norms	ACS
Warranty	



ADVANTAGES

-  Thermostatic temperature regulation
-  Instant shut-off if cold water fails
-  Fixed shower head or handset
-  Stainless steel sheath, brass controls

