

SECURITHERM dual control shower panel

Ref. 792354CF

Mechanical thermostatic dual control, comfort 10 lpm

DESCRIPTION

SECURITHERM dual control shower panel - Ref. 792354CF

Dual control thermostatic shower panel:
Large model stainless steel shower panel for wall mounted, exposed installation.
Concealed inlet via flexibles M $\frac{1}{2}$ ".
SECURITHERM thermostatic mixer.
Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.
Anti-scalding failsafe: automatic shut-off if cold or hot water supply fails.
Anti-cold showers function: automatic shut-off if hot water fails.
Chrome-plated, tamperproof, fixed, ROUND shower head with scale-resistant nozzle and automatic flow rate regulation at 10 lpm at 3 bar.
Handset with removable flexible via rapid push-fit STOP connector, wall support supplied.
Non-time flow valves to control the ROUND shower head and the handset.
Thermal shocks are possible.
Stopcocks.
Concealed fixings.
Filters and non-return valves.
30-year warranty.





TECHNICAL CHARACTERISTICS

SECURITHERM dual control shower panel - Ref. 792354CF

Connector	M $\frac{1}{2}$ "
Technology	Non-Time flow
Height	1,220mm
Depth	100mm
Width	250mm
Flow rate	10 lpm
Temperature limiter	Thermostatic
Finish	Stainless steel
Norms	ACS
Warranty	



ADVANTAGES

-  Thermostatic temperature regulation
-  Instant shut-off if cold water fails
-  Fixed shower head or handset
-  Stainless steel sheath, brass controls

