Shower riser rail with EP mechanical mixer

Ref. 2239EPSKIT

Riser rail with pressure-balancing mixer



DESCRIPTION

Shower riser rail with EP mechanical mixer - Ref. 2239EPSKIT

Shower riser rail with single control mechanical mixer.
• Wall-mounted shower kit.
Ø 40mm ceramic cartridge with pressure-balancing (EP) and pre-set maximum temperature limiter.
Total anti-scalding safety: HW flow rate is reduced if CW supply fails (and vice versa).
Constant temperature regardless of pressure or flow rate variations.
Flow rate regulated at 9 lpm.
Chrome-plated brass body and sculptured control lever.
M½" shower outlet with integrated non-return valve.
Mixer with 2 offset standard wall connectors M1/2" M3/4".
Filters and non-return valves
• Chrome-plated sliding shower head (ref. 811) on a chrome-plated riser rail (ref. 820) with soap dish and flexible hose (ref. 834T1).
Shower riser rail ideal for healthcare facilities, nursing homes, hospitals and clinics.
Suitable for people with reduced mobility.
30-year warranty.

ADVANTAGES

- HW flow rate reduced if CW fails
- Pressure-balancing: constant temperature
- Ergonomic: sculptured lever is easy to grip
- Water savings: flow rate regulated at 9 lpm

TECHNICAL CHARACTERISTICS

Shower riser rail with EP mechanical mixer - Ref. 2239EPSKIT

Connector	M1/2"
Technology	SECURITHERM EP
Width	175mm
Flow rate	9 lpm
Temperature limiter	39°C
Finish	Chrome-plated brass
Norms	ACS, BELGAQUA
Warranty	30 YEAR WARRANTY
Repairability	50 YEARS REPAIRABILITY

