

## TEMPOMIX 3 time flow mixer

Ref. 794160

Soft-touch operation, stopcocks



### DESCRIPTION

**TEMPOMIX 3 time flow mixer - Ref. 794160**

Wall-mounted single control time flow basin mixer:  
 Soft-touch operation.  
 Temperature control and operation via the push-button.  
 Time flow pre-set at ~7 seconds.  
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.  
 Tamperproof, scale-resistant flow straightener.  
 Chrome-plated solid brass body L. 110mm.  
 For cross wall installation.  
 PEX flexibles F3/8" with stopcocks, filters and non-return valves.  
 Adjustable maximum temperature limiter.  
 Suitable for people with reduced mobility.  
 30-year warranty.

### TECHNICAL CHARACTERISTICS

**TEMPOMIX 3 time flow mixer - Ref. 794160**

|              |   |
|--------------|---|
| Connector    | F3/8"   |
| Technology   | Time flow   |
| Spout length | 110mm   |
| Flow rate    | 3 lpm   |
| Norms        |     |
| Warranty     |    |

### ADVANTAGES

-  Exceptional water savings: 85%
-  Soft-touch operation
-  Solid brass; install behind the partition
-  Sleek design

