

# SECURITHERM EP pressure-balancing shower mixer

Ref. 2539EPS

Wall-mounted single control mixer, sculptured lever



## DESCRIPTION

**SECURITHERM EP pressure-balancing shower mixer - Ref. 2539EPS**

Wall-mounted single control mechanical shower mixer.  
Ø 40mm ceramic cartridge with pressure-balancing and pre-set maximum temperature limiter.

Anti-scalding safety: HW flow rate is reduced if CW supply fails (and vice versa).

Stable temperature regardless of pressure and flow rate variations in the system.

Flow rate regulated at 9 lpm.

M $\frac{1}{2}$ " shower outlet with integrated non-return valve.

Mixer with offset standard wall connectors M $\frac{1}{2}$ " M $\frac{3}{4}$ ".

Filters and non-return valves.

Mechanical mixer with SECURITHERM pressure-balancing ideal for healthcare facilities, nursing homes, hospitals and clinics.

Shower mixer suitable for people with reduced mobility.

Mixer with 30-year warranty.

## ADVANTAGES



HW flow rate reduced if CW fails



Pressure-balancing: limits temperature variations








Ergonomic: sculptured lever is easy to grip



Water savings: flow rate regulated at 9 lpm

## TECHNICAL CHARACTERISTICS

**SECURITHERM EP pressure-balancing shower mixer - Ref. 2539EPS**

|                     |   |
|---------------------|---|
| Connector           | M1/2"   |
| Technology          | SECURITHERM EP mechanical mixer   |
| Flow rate           | 9 lpm   |
| Temperature limiter | Yes   |
| Finish              | Chrome-plated brass   |
| Norms               | ACS    |
| Warranty            |    |
| Repairability       |    |

