

SECURITHERM EP pressure-balancing shower mixer

Ref. 2239EP

Wall-mounted single control mixer, sculptured lever



DESCRIPTION

SECURITHERM EP pressure-balancing shower mixer - Ref. 2239EP

Wall-mounted single control mechanical mixer.
 Ø 40mm ceramic cartridge with pressure-balancing and pre-set maximum temperature limiter.
 Total anti-scalding safety: HW flow rate is reduced if CW supply fails (and vice versa).
 Stable temperature regardless of pressure and flow rate variations in the system.
 Flow rate regulated at 9 lpm.
 Chrome-plated brass body and sculptured control lever.
 M½" shower outlet with integrated non-return valve.
 Mixer with offset STOP/CHECK wall connectors M½" M¾".
 Filters and non-return valves.
 Mechanical mixer with SECURITHERM pressure-balancing ideal for healthcare facilities, nursing homes, hospitals and clinics.
 Shower mixer suitable for people with reduced mobility.
 Mixer with 30-year warranty.

ADVANTAGES



HW flow rate reduced if CW fails



Pressure-balancing: limits temperature variations



Ergonomic: sculptured lever is easy to grip



Water savings: flow rate regulated at 9 lpm

TECHNICAL CHARACTERISTICS

SECURITHERM EP pressure-balancing shower mixer - Ref. 2239EP

Connector	M1/2"
Technology	SECURITHERM EP mechanical mixer
Width	175mm
Flow rate	9 lpm
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	   
Warranty	
Repairability	

