## BINOPTIC MIX electronic mixer

Ref. 488MCHLH15

Battery-operated, Ø 15mm compression fittings



## **DESCRIPTION**

BINOPTIC MIX electronic mixer - Ref. 488MCHLH15

Deck-mounted electronic basin mixer:

Independent IP65 electronic control unit.

123 6V Lithium batteries.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.

Scale-resistant flow straightener.

Adjustable duty flush (pre-set flush 60 seconds every 24 hours after last use). Active, infrared presence detection, sensor at the end of the spout optimises detection.

Chrome-plated brass body.

PEX flexibles with filters and solenoid valve Ø 15mm compression fittings. Fixing reinforced by 2 stainless steel rods.

Anti-blocking security.

Spout with smooth interior and low water volume (reduces bacterial development).

Side temperature control with long lever and adjustable maximum temperature limiter.

Drop height: 170mm for semi-recessed washbasins.

Suitable for people with reduced mobility.

30-year warranty.

## **ADVANTAGES**



Exceptional water savings: 90%



Hygiene: no manual contact



Anti-bacterial duty flush




LED diagnostic aid

## **TECHNICAL CHARACTERISTICS**

BINOPTIC MIX electronic mixer - Ref. 488MCHLH15

Supply	6V batteries
Connector	M1/2" Ø 15
Technology	Electronic
Drop height	170mm
Spout length	175mm
Flow rate	3 lpm
Norms	<b>♦WRAS</b>
Warranty	30 g



© DELABIE https://www.delabie.co.uk