

# BINOPTIC MIX electronic mixer

Ref. 498MCHLH15

Battery-operated, Ø 15mm compression fittings

## DESCRIPTION

**BINOPTIC MIX electronic mixer - Ref. 498MCHLH15**

Deck-mounted electronic basin mixer:  
Independent IP65 electronic control unit.  
123 6V Lithium batteries.  
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.  
Scale-resistant flow straightener.  
Adjustable duty flush (pre-set flush 60 seconds every 24 hours after last use).  
Active, infrared presence detection, sensor at the end of the spout optimises detection.  
Chrome-plated brass body.  
PEX flexibles with filters and solenoid valves Ø 15mm compression fittings.  
Fixing reinforced by 2 stainless steel rods.  
Anti-blocking security.  
Spout with smooth interior and low water volume (reduces bacterial development).  
Side temperature control with long lever and adjustable maximum temperature limiter.  
Drop height: 250mm for counter-top washbasins.  
Suitable for people with reduced mobility.  
30-year warranty.

## TECHNICAL CHARACTERISTICS

**BINOPTIC MIX electronic mixer - Ref. 498MCHLH15**

Supply	6V batteries
Connector	M1/2" Ø 15mm
Technology	Electronic
Drop height	250mm
Spout length	185mm
Flow rate	3 lpm
Norms	
Warranty	
Repairability	



## ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Anti-bacterial duty flush



LED diagnostic aid

