

# Be-Line® drop-down support rail, L. 850mm, anthracite

Ref. 511964C

Powder-coated metallised anthracite



## DESCRIPTION

**Be-Line® drop-down support rail, L. 850mm, anthracite - Ref. 511964C**

Be-Line® drop-down support rail for people with reduced mobility.

In the lowered position use as a grab bar, as a support for standing and for assisting movement, for WCs or showers.

Allows side access in the raised position.

Removable: easy to remove with anti-theft locking system. Reduces the number of grab bars in a facility, allowing installation only when required.

Example: hotels or hospitals providing short-term accommodation for disabled people.

Drop-down rail with slowed down descent. Retained in upright position.

Aluminium tube.

Rounded profile Ø 42mm with ergonomic flat front face that prevents rotation for an optimal grip.

Metallised anthracite powder-coated aluminium finish provides a good visual contrast with light-coloured walls.

Uniform surface for easy maintenance and hygiene.

Concealed fixings secured to wall by a 304 stainless steel plate, 5mm thick.

Supplied with stainless steel screws Ø 8 x 70mm for concrete walls.

Dimensions: 850 x 210 x 120mm.

Tested to over 200kg. Maximum recommended user weight: 135kg.

Support rail for WCs with 30-year warranty.

CE marked.

## ADVANTAGES



Innovative design suitable for all users



Removable: easy to unclip



Comfort: ergonomic flat face prevents rotation



Tested to over 200kg

## TECHNICAL CHARACTERISTICS

**Be-Line® drop-down support rail, L. 850mm, anthracite - Ref. 511964C**

|          |                                                                                        |
|----------|----------------------------------------------------------------------------------------|
| Height   | 210mm, 920mm when raised                                                               |
| Length   | 850mm                                                                                  |
| Width    | 120mm                                                                                  |
| Diameter | Ø 42mm                                                                                 |
| Finish   | Powder-coated metallised anthracite aluminium                                          |
| Norms    | CE  |
| Warranty |     |

