Mechanical sink mixer

Ref. 2447LUK

Wall-mounted mixer, fixed L. 150mm spout, Hygiene lever L. 150mm



DESCRIPTION

Mechanical sink mixer - Ref. 2447LUK

Wall-mounted mechanical basin mixer, 200mm centres.

Flat fixed under spout L. 150mm with hygienic flow straightener suitable for fitting a BIOFIL terminal filter.

Securitouch thermal insulation prevents burns.

 \emptyset 40mm ceramic cartridge with pre-set maximum temperature limiter.

Body and spout with smooth interiors and low water volume (reduce niches where bacteria can develop).

Flow rate regulated at 5 lpm.

Chrome-plated brass body.

Hygiene control lever L. 150mm.

Supplied with in-line STOP/CHECK connectors M1/2" M3/4" ideal for hospitals. 30-year warranty.

TECHNICAL CHARACTERISTICS

Mechanical sink mixer - Ref. 2447LUK

| Connector | M1/2" |
|--------------|---------------------|
| Technology | Securitouch |
| Spout length | 150mm |
| Flow rate | 5 lpm |
| | |
| Finish | Chrome-plated brass |
| Finish Norms | Chrome-plated brass |
| | · |

ADVANTAGES



Smooth interior body/spout reduces bacteria




Pre-set maximum temperature



Securitouch thermal insulation prevents burns



Hygiene control lever requires no manual contact



© DELABIE https://www.delabie.co.uk