

SECURITHERM EP pressure-balancing basin mixer

Ref. 2447LEPUK

Wall-mounted mixer, fixed L. 150mm spout, Hygiene lever L. 150mm



DESCRIPTION

SECURITHERM EP pressure-balancing basin mixer - Ref. 2447LEPUK

SECURITHERM pressure-balancing wall-mounted mechanical sink mixer, 200mm centres.

Anti-scalding safety: HW flow rate is reduced if CW flow rate fails (and vice versa).

Securitouch thermal insulation prevents burns.

Flat fixed under spout L. 150mm with hygienic flow straightener suitable for fitting a BIOFIL terminal filter.

Ø 40mm pressure-balancing ceramic cartridge with pre-set maximum temperature limiter.

Body and spout with smooth interiors and low water volume (reduce niches where bacteria can develop).

Flow rate regulated at 5 lpm.

Chrome-plated brass body.

Hygiene control lever L. 150mm.

Supplied with in-line STOP/CHECK connectors M1/2" M3/4" ideal for hospitals. 30-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM EP pressure-balancing basin mixer - Ref. 2447LEPUK

Connector	M1/2"
Technology	SECURITHERM EP, Securitouch
Spout length	150mm
Flow rate	5 lpm
Temperature limiter	41°C
Finish	Chrome-plated brass
Norms	
Warranty	
Repairability	

ADVANTAGES



Anti-scalding safety: HW flow reduced if CW fails



Securitouch thermal insulation prevents burns



Pre-set maximum temperature limiter



Smooth interior body/spout reduces bacteria

