

TEMPOFIX 3 self-supporting frame system with time flow WC valve

Ref. 564065DE-763040

TEMPOFLUX 3 AB dual flush 3L/6L time flow valve - Ø 110mm soil pipe

DESCRIPTION

TEMPOFIX 3 self-supporting frame system with time flow WC valve - Ref. 564065DE-763040

Self-supporting frame system W.350mm for wall-hung WCs:

- Black powder-coated steel frame.
 - Fixes to load-bearing floors.
 - Frame height can be adjusted from 0 - 200mm (with 1m mark).
 - Ø 32mm flush tube with Ø 55mm connection washer.
 - ABS soil pipe, Ø 110mm HDPE outlet with waterproof seal, with 2 setting positions.
 - Delivered pre-mounted.
 - Compatible with solid walls from 10 - 120mm.
- Fitted with TEMPOFLUX 3 3/4" time flow direct flush valve:
- Chrome-plated metal wall plate 170 x 170mm.
 - Waterproof recessing housing.
 - Soft-touch operation.
 - Dual flush 3L/6L, can be adjusted to 2L/4L.
 - AB anti-blocking system.
 - Backflow prevention device inside the housing.
 - Integrated stopcock and flow rate adjuster.
 - Acoustic level complies with European standard EN 12541 class II.
 - Compatible with sea water and grey water.
 - 10-year warranty.

Technical features: see TEMPOFLUX 3 ref. 763BOX-763040.


Kit contents:

(564065DE): frame system, soil pipe Ø 110mm, flush tube, recessed housing with cover, valve configured for system flush, vacuum breaker, stopcock, connection accessories.

(763040): control plate, collar for waterproofing, time flow cartridge.

TECHNICAL CHARACTERISTICS

TEMPOFIX 3 self-supporting frame system with time flow WC valve - Ref. 564065DE-763040

Connector	3/4"
Technology	Time flow
Height	1000-1320mm
Depth	187 mm
Width	350mm
Finish	Chrome-plated metal
Warranty	



ADVANTAGES



Quick and easy to install: delivered pre-mounted



Self-supporting frame system



Dual flush 3L/6L, anti-blocking system



Direct flush: no stagnant water

