

TEMPOMATIC 4 urinal valve

Ref. 479413

Electronic with integrated batteries

DESCRIPTION

TEMPOMATIC 4 urinal valve - Ref. 479413

Exposed electronic urinal valve with integrated batteries:

Battery-operated with integrated CR 123 6V Lithium batteries.

For wall-mounted, exposed installation.

Reduced-stagnation solenoid valve and electronic unit integrated into the valve body.

Shockproof infrared presence detection sensor.

Detection delay is 10 sec.

3 programmes (rinsing volume adjustable in accordance to the type of urinal).

High-frequency mode (exclusive to DELABIE):

- short rinse after each user

- complementary rinse after busy period.

Hygienic duty flush, every 24hr after last use, prevents vacuums in the siphon.

Compatible with rain water.

Flow rate 0.15 L/sec. at 3 bar, can be adjusted.

Integrated stopcock and flow rate adjuster.

One-piece chrome-plated metal body.

M $\frac{1}{2}$ " connection.

Angled for recessed supply.

For DELABIE FINO urinal.

Suitable for people with reduced mobility.

30-year warranty.

Ideal for replacing old installations:

Can easily be installed where there was previously a time flow urinal.

TECHNICAL CHARACTERISTICS

TEMPOMATIC 4 urinal valve - Ref. 479413

Supply	6V batteries
Connector	M $\frac{1}{2}$ "
Technology	Electronic
Height	465mm
Depth	85mm
Flow rate	0.15 l/sec.
Norms	CE
Warranty	30 YEAR WARRANTY



ADVANTAGES



Total hygiene: no manual contact



High-frequency mode



Batteries integrated into the valve body



Hygienic duty flush

