

# SECURITHERM EP pressure-balancing basin mixer

Ref. 2870T1EP

Tall single hole, single control mixer with EP cartridge

## DESCRIPTION

**SECURITHERM EP pressure-balancing basin mixer - Ref. 2870T1EP**

Deck-mounted SECURITHERM pressure-balancing, tall basin mixer. Single hole, single control mixer with high, swivelling spout H. 180mm. Mixer supplied with 2 removable stainless steel spouts. Anti-scalding safety: reduced HW flow if CW supply fails (and vice versa). Ø 35mm ceramic cartridge with pressure-balancing and pre-set maximum temperature limiter. Body and spout with smooth interiors (limits bacterial development). Thermal shocks are possible without removing the control lever or shutting off the cold water supply. Flow rate limited to 5 lpm at 3 bar. Body and base in chrome plated brass. Hygiene control lever L. 185mm requires no manual contact. PEX flexibles F3/8" with filters and non-return valves. Reinforced fixing by 2 stainless steel rods. Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics. Suitable for people with reduced mobility. 30-year warranty.

## TECHNICAL CHARACTERISTICS

**SECURITHERM EP pressure-balancing basin mixer - Ref. 2870T1EP**

|               |                                                                                                                                                                         |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connector     | F3/8"                                                                                                                                                                   |
| Technology    | BIOCLIP                                                                                                                                                                 |
| Drop height   | 180mm                                                                                                                                                                   |
| Spout length  | 185mm                                                                                                                                                                   |
| Flow rate     | 5 lpm                                                                                                                                                                   |
| Finish        | Chrome-plated brass                                                                                                                                                     |
| Norms         |   |
| Warranty      |                                                                                      |
| Repairability |                                                                                      |



## ADVANTAGES



Hygiene: smooth interior reduces bacteria



Thermal shock possible without removing lever



Pre-set maximum temperature limiter



Hygiene control lever requires no manual contact

