

## Mechanical mixer for sinks or troughs

Ref. 2510

Single hole mechanical mixer with swivelling spout H. 155mm L. 230mm







### DESCRIPTION

**Mechanical mixer for sinks or troughs - Ref. 2510**

Deck-mounted mechanical sink mixer.  
 Single hole mixer with swivelling spout H. 155mm L. 230mm fitted with hygienic flow straightener.  
 Spout suitable for fitting a BIOFIL point-of-use filter.  
 Ø 40mm standard ceramic cartridge with pre-set maximum temperature limiter.  
 Body and spout with smooth interiors.  
 No risk of cross flow between the hot and cold water.  
 No non-return valves on the inlets.  
 Body and spout made from chrome-plated brass.  
 Flow limited to 9 lpm at 3 bar.  
 Sculptured control lever.  
 Supplied with PEX flexibles F3/8".  
 Fixing reinforced by 2 stainless steel rods.  
 Mechanical mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.  
 Single hole mixer suitable for people with reduced mobility.  
 Mixer with 30-year warranty.





### TECHNICAL CHARACTERISTICS

**Mechanical mixer for sinks or troughs - Ref. 2510**

Connector	F3/8"
Height	178mm
Drop height	155mm
Spout length	230mm
Flow rate	9 lpm at 3 bar
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	   
Warranty	
Repairability	



### ADVANTAGES

- 
 Hygiene: smooth interior reduces bacteria
- 
 Pre-set maximum temperature limiter
- 
 Ergonomic sculptured control lever is easy to grip
- 
 Comfort: optimum drop height and spout projection

