

## TEMPOMIX 3 time flow mixer

Ref. 794000

Soft-touch operation, stopcocks



### DESCRIPTION

TEMPOMIX 3 time flow mixer - Ref. 794000

Deck-mounted single control time flow basin mixer:  
Soft-touch operation.  
Temperature control and operation on the push-button.  
Time flow pre-set at ~7 seconds.  
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.  
Tamperproof scale-resistant flow straightener.  
Chrome-plated metal body.  
PEX flexibles F3/8" with stopcocks, filters and non-return valves.  
Fixing reinforced by 2 stainless steel rods.  
Adjustable maximum temperature limiter.  
Suitable for people with reduced mobility.  
30-year warranty.

### TECHNICAL CHARACTERISTICS

TEMPOMIX 3 time flow mixer - Ref. 794000

|               |                                                                                                                                                                                                                                                                                                                                                 |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connector     | F3/8"                                                                                                                                                                                                                                                                                                                                           |
| Technology    | Time flow                                                                                                                                                                                                                                                                                                                                       |
| Drop height   | 70mm                                                                                                                                                                                                                                                                                                                                            |
| Spout length  | 105mm                                                                                                                                                                                                                                                                                                                                           |
| Flow rate     | 3 lpm                                                                                                                                                                                                                                                                                                                                           |
| Norms         |     |
| Warranty      |                                                                                                                                                                                                                                                              |
| Repairability |                                                                                                                                                                                                                                                              |

### ADVANTAGES



Exceptional water savings: 85%



Soft-touch operation



Sleek lines



Sleek design

