# TEMPOMIX 3 time flow mixer

Ref. 794350

Soft-touch operation



## DESCRIPTION

**TEMPOMIX 3 time flow mixer** - Ref. 794350

Wall-mounted single control time flow basin mixer:
Soft-touch operation.
Temperature control and operation via the push-button.
Time flow pre-set at ~7 seconds.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 3 - 6 lpm.
Scale-resistant flow straightener.
Chrome-plated metal body M½".
Swivelling spout L. 150mm.
Filters and non-return valves.
Adjustable maximum temperature limiter.
M½" offset connectors for centres from 130 - 170mm.
Suitable for people with reduced mobility.
30-year warranty.

## ADVANTAGES

- Exceptional water savings: 85%
- Soft-touch operation
- Sleek and slim design

## TECHNICAL CHARACTERISTICS

**TEMPOMIX 3 time flow mixer** - Ref. 794350

| | |
|---|---|
| Connector | M1/2" |
| Technology | Time flow |
| Length | 200mm |
| Width | 150mm |
| Spout length | 150mm |
| Flow rate | 3 lpm |
| Norms | ACS, BELGAQUA, WRAS |
| Warranty | 30 YEAR WARRANTY |
| Repairability | 50 YEARS REPAIRABILITY |




