

TEMPOFLUX 1 direct flush valve

Ref. 761110

Time flow direct flush WC valve



DESCRIPTION

TEMPOFLUX 1 direct flush valve - Ref. 761110

Time flow direct flush valve for cross wall installation:
 For walls ≤ 200mm.
 Soft-touch operation.
 Time flow ~7 seconds.
 Vacuum breaker.
 Stopcock and flow rate/volume adjuster are integrated.
 Chrome plated metal body.
 Inline inlet M $\frac{3}{4}$ ".
 Connection washer Ø 32/55mm.
 Threaded rod can be cut to size.
 Upstream supply pipes: minimum Ø 20mm required at all points (including connectors).
 Base flow rate: 1 l/sec at 1 bar dynamic pressure.
 Compatible with rain water.
 Suitable for people with reduced mobility.
 30-year warranty.
 [Formerly ref: 761200]

ADVANTAGES

-  No cistern: no stagnant water
-  Cross wall installation
-  Powerful flush is immediately available
-  Direct flush reduces the risk of leaks

TECHNICAL CHARACTERISTICS

TEMPOFLUX 1 direct flush valve - Ref. 761110

Connector	$\frac{3}{4}$ "
Technology	Time flow
Length	200mm
Norms	
Warranty	

