

# TEMPOFLUX 1 direct flush valve

Ref. 761110

Time flow direct flush WC valve





## DESCRIPTION

TEMPOFLUX 1 direct flush valve - Ref. 761110


Time flow direct flush valve for cross wall installation:  
 For walls ≤ 200mm.  
 Soft-touch operation.  
 Time flow ~7 seconds.  
 Vacuum breaker.  
 Stopcock and flow rate/volume adjuster are integrated.  
 Chrome plated metal body.  
 Inline inlet M $\frac{3}{4}$ ".  
 Connection washer Ø 32/55mm.  
 Threaded rod can be cut to size.  
 Upstream supply pipes: minimum Ø 20mm required at all points (including connectors).  
 Base flow rate: 1 l/sec at 1 bar dynamic pressure.  
 Compatible with rain water.  
 Suitable for people with reduced mobility.  
 30-year warranty.  
 [Formerly ref: 761200]

## ADVANTAGES

-  No cistern: no stagnant water
-  Cross wall installation
-  Powerful flush is immediately available
-  Direct flush reduces the risk of leaks

## TECHNICAL CHARACTERISTICS

TEMPOFLUX 1 direct flush valve - Ref. 761110

Connector	$\frac{3}{4}$ "
Technology	Time flow
Length	200mm
Norms	
Warranty	