

Mechanical mixer for sinks or troughs

Ref. 2564T4

High swivelling spout H. 300mm L. 250mm

DESCRIPTION

Mechanical mixer for sinks or troughs - Ref. 2564T4

Deck-mounted mechanical sink mixer.
 Single hole, single control mixer with swivelling spout H. 305mm L. 220mm.
 Tall mixer with hygienic flow straightener suitable for fitting a BIOFIL terminal filter.
 Ø 35mm classic ceramic cartridge with pre-set maximum temperature limiter.
 Body and spout with smooth interiors (reduced bacterial development).
 No risk of cross flow between the hot and cold water.
 No non-return valves on the inlets.
 Thermal shocks are easy to undertake without removing the control lever or shutting off the cold water supply.
 Flow rate limited to 9 lpm at 3 bar.
 Chrome-plated brass body and spout.
 Hygiene control lever L. 185mm requires no manual contact.
 PEX flexibles F3/8".
 Fixings reinforced by 2 stainless steel rods and back-nuts.
 Mechanical mixer ideal for people with healthcare facilities, retirement and care homes, hospitals and clinics.
 Single hole mixer suitable for people with reduced mobility.
 Mixer with 30-year warranty.

TECHNICAL CHARACTERISTICS

Mechanical mixer for sinks or troughs - Ref. 2564T4

Connector	F3/8"
Height	462mm
Drop height	305mm
Spout length	220mm
Flow rate	9 lpm at 3 bar
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	   
Warranty	
Repairability	



ADVANTAGES

- 
Hygiene: smooth interiors reduce bacteria
- 
Thermal shock without removing the control lever
- 
Pre-set maximum temperature limiter
- 
No manual contact thanks to Hygiene control lever

