# Mechanical mixer for sinks or troughs

Ref. 2564T4

High swivelling spout H. 300mm L. 250mm



## DESCRIPTION

**Mechanical mixer for sinks or troughs - Ref. 2564T4**

Deck-mounted mechanical sink mixer.
Single hole, single control mixer with swivelling spout H. 305mm L. 220mm.
Tall mixer with hygienic flow straightener suitable for fitting a BIOFIL terminal filter.
Ø 35mm classic ceramic cartridge with pre-set maximum temperature limiter.
Body and spout with smooth interiors (reduced bacterial development).
No risk of cross flow between the hot and cold water.
No non-return valves on the inlets.
Thermal shocks are easy to undertake without removing the control lever or shutting off the cold water supply.
Flow rate limited to 9 lpm at 3 bar.
Chrome-plated brass body and spout.
Hygiene control lever L. 185mm requires no manual contact.
PEX flexibles F3/8".
Fixings reinforced by 2 stainless steel rods and back-nuts.
Mechanical mixer ideal for people with healthcare facilities, retirement and care homes, hospitals and clinics.
Single hole mixer suitable for people with reduced mobility.
Mixer with 30-year warranty.

## ADVANTAGES

- Hygiene: smooth interiors reduce bacteria
- Thermal shock without removing the control lever
- Pre-set maximum temperature limiter
- No manual contact thanks to Hygiene control lever

## TECHNICAL CHARACTERISTICS

**Mechanical mixer for sinks or troughs - Ref. 2564T4**

| | |
|---|---|
| Connector | F3/8" |
| Height | 462mm |
| Drop height | 305mm |
| Spout length | 220mm |
| Flow rate | 9 lpm at 3 bar |
| Temperature limiter | Yes |
| Finish | Chrome-plated brass |
| Norms | ACS, WRAS |
| Warranty | 30 YEARS WARRANTY |
| Repairability | 50 YEARS REPAIRABILITY |

