SECURITHERM time flow shower kit



Ref. 792219

Thermostatic time flow, kit 2/2



DESCRIPTION

SECURITHERM time flow shower kit - Ref. 792219

Recessed thermostatic time flow shower, kit 2/2:
Tamperproof polished satin stainless steel plate 195 x 220mm.
SECURITHERM thermostatic mixer ¾".
Anti-scalding failsafe: automatic shut-off if cold water fails.
Anti-cold showers function: automatic shut-off if hot water fails.
Adjustable temperature from 32° to 40°C, pre-set at 38°C.
Soft-touch operation.
Time flow ~30 seconds.
Flow rate set at 6 lpm at 3 bar.
Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.
Concealed fixings, M½" stopcocks.
Integrated non-return valves and filters.
Chrome-plated Bayblend® control knob.
Suitable for people with reduced mobility.
30-year warranty.
Order with waterproof housing ref. 792BOX.

ADVANTAGES

- Thermostatic temperature control
- Instant shut-off if cold water fails
- 80% water savings

TECHNICAL CHARACTERISTICS

SECURITHERM time flow shower kit - Ref. 792219

Connector	½"
Technology	Time flow
Height	195mm
Depth	110mm
Width	220mm
Flow rate	6 lpm
Finish	Satin finish stainless steel
Norms	ACS
Warranty	30 YEAR WARRANTY

