

SECURITHERM time flow shower kit

Ref. 792219

Thermostatic time flow, kit 2/2

DESCRIPTION

SECURITHERM time flow shower kit - Ref. 792219

Recessed thermostatic time flow shower, kit 2/2:
 Tamperproof polished satin stainless steel plate 195 x 220mm.
 SECURITHERM thermostatic mixer ¾".
 Anti-scalding failsafe: automatic shut-off if cold water fails.
 Anti-cold showers function: automatic shut-off if hot water fails.
 Adjustable temperature from 32° to 40°C, pre-set at 38°C.
 Soft-touch operation.
 Time flow ~30 seconds.
 Flow rate set at 6 lpm at 3 bar.
 Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.
 Concealed fixings, M½" stopcocks.
 Integrated non-return valves and filters.
 Chrome-plated Bayblend® control knob.
 Suitable for people with reduced mobility.
 30-year warranty.
 Order with waterproof housing ref. 792BOX.

TECHNICAL CHARACTERISTICS

SECURITHERM time flow shower kit - Ref. 792219

Connector	½"
Technology	Time flow
Height	195mm
Depth	110mm
Width	220mm
Flow rate	6 lpm
Finish	Satin finish stainless steel
Norms	  
Warranty	



ADVANTAGES



Thermostatic temperature control



Instant shut-off if cold water fails



80% water savings

